Configure a Geocoding Service

To configure a Spatial NI geocoding service in your organisational ArcGIS Enterprise (Portal):

- 1. Log in to your organisational ArcGIS Enterprise (Portal)
- 2. Navigate to Organisation tab
- 3. Select the Settings option
- 4. From the list, select Utility Services

General
Home Page
Gallery
Map
Items
Groups
Utility Services
Member Roles
Marketplace
Collaborations
Credits
Security
Open Data

- 5. Scroll to the Geocoding section and click Add Locator
- 6. From the dialog box that opens, configure the following options:

Add Locator	\times
ArcGIS World Geocoding Service	
New Locator	
From URL From Existing Locator	
Locator URL	
Example: https://webadaptor.domain.com/arcgis/rest/services/folder/ser vicename/GeocodeServer	
Locator Name My Locator	
Placeholder Text Find address or place	
Allow geosearchAllow batch geocoding	
OK Car	ncel



Configure a Geocoding Service:

ArcGIS Enterprise

- Select the radio button beside New Locator
- Select the radio button beside From URL
- Enter the URL provided by Spatial NI (it will start with https://utility.arcgis.com/)
- Give the locator a name (e.g. OSNI Pointer Locator)

Configure the other options if required

- 7. Click OK
- 8. Your new locator should now appear in the list of Geocoding services

Geocoding		
Q	Establish the <u>locators</u> that members of your organization will have a name, and set other properties. You can also reorder, configure, or Add Locator	iccess to. Click Add Locator to reference a URL, specify a user friendly delete your locators below.
	Name	
	Pointer Locator (Premium)	/ ×

- Remove the ESRI World Geocoding service if you just want the OSNI one available. To do this click the red X beside its name in the list.
- 10. Scroll to the bottom of the page and click Save



Configure a Geocoding Service:

ArcGIS Enterprise